



ML240P SERIES

Simplicity and Agility Just One Step Away

TSC ML240P Series is a brand new generation of industrial barcode label printers. The light industrial ML240P Series features ease of use, intuitive color GUI display, noise-reduced printing, and self-diagnostic TPH Care. The ML240P Series has a durable and flexible design and does not require special tools for performing common service and maintenance.

Its compact footprint is perfect for crowded work environments. The ML240P Series is designed for durability while producing high quality printed labels. With its enhanced design and printing algorithm, the noise level from printing operation is dramatically reduced. The adjustable thermal printhead and self-diagnostic TPH Care mechanism ensure optimal print quality regardless of the application or label design.

KEY FEATURES



Streamlined and Small Footprint Design

- Brand new compact design
- Small footprint fits easily into more spaces and fits in limited operation areas



Robust and Agile Design for Optimal Quality

- The combination of rugged die-cast, modularized base and adjustable TPH module design structure optimizes print quality



Noise-Reduction Printing Engineering

- Its enhanced design and printing algorithm feature results in a quieter and smoother printing operation



Self-Diagnostic TPH Care Mechanism

- An advanced mechanism allows for real-time printhead health status to ensure stable and high quality printouts for maximum cost-effectiveness



Effortless User Operation with Color Display

- Wide open angle for easy media handling
- Ease of use 2.3" color GUI display and intuitive indicator



One Step Maintenance

- Tool-less removal and replacement of the printhead and platen roller saves time

APPLICATIONS



Manufacturing

- Work In Process
- Product Marking
- Compliance Labeling



Warehouse & Logistics

- Packing
- Order Fulfilment
- Shipping/Receiving
- Inventory Management



Healthcare

- Blood Test Tube Label
- Patient Wristband Label



Retail

- Product Label
- Event Ticketing

ML240P SERIES – Industrial Thermal Transfer Bar Code Printer

PRINTER MODEL	ML240P	ML340P
Resolution	8 dots/mm (203 DPI)	12 dots/mm (300 DPI)
Printing method	Thermal Transfer & Direct Thermal	
Max. print speed	152 mm (6")/second	127 mm (5")/second
Max. print width	108 mm (4.25")	105.7mm (4.16")
Max. print length	2,794 mm (110")	1,016 mm (40")
Enclosure	Die-cast print mechanism/Metal cover with large media window	
Physical dimension	248 mm (W) x 245 mm (H) x 330 mm (D) 9.76" (W) x 9.65" (H) x 12.99" (D)	
Weight	7.6 kg (16.76 lbs)	
Label roll capacity	139.7 mm (5.5") O.D., 1" or 1.5" I.D core	
Ribbon	450 m long, max. O.D. 81.3 mm, 1" core (ink coated outside or inside)	
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3")	
Processor	32-bit RISC CPU	
Memory	• 128 MB Flash memory • 64 MB SDRAM	
Interface	• RS-232 • USB 2.0 • Internal Ethernet, 10/100 Mbps • USB host, for scanner or PC keyboard • Internal Bluetooth 4.2 (dealer option) • Slot-in 802.11 a/b/g/n wireless (dealer option)*	
Display	• 2.3" color LCD • 1 status indicator	
Operation switch, button	• 6 buttons (Menu, Pause/Feed, Up, Down, Left, Right)	
Sensors	• Gap transmissive sensor (position adjustable) • Black mark reflective sensor (position adjustable) • Ribbon end sensor • Head open sensor	
Real time clock	Standard	
Internal fonts	• 8 alpha-numeric bitmap fonts • Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font	
Bar code	• 1D bar code Code 11, Code 39, Code 49, Code 93, Code128UCC, Code128 subsets A.B.C, Codabar, Standard 2 of 5, Industrial 2 of 5, Interleave 2 of 5, EAN-8, EAN-13, EAN-14, EAN-128, ITF14, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, PLANET, POSTNET, RSS-Stacked, GS1 DataBar, China Post, Telepen, LOGMARS • 2D bar code PDF-417, Micro PDF 417, Maxicode, DataMatrix, QR code, Aztec, TLC 39, RSS	
Font and barcode rotation	0, 90, 180, 270 degree	
Printer language	TSPL-EZD (Compatible to EPL, ZPL, ZPL II, DPL)	
Media type	Continuous, die-cut, black mark, fan-fold, notched (outside wound)	
Media width	20 ~ 118 mm (0.8" ~ 4.7") 20 ~ 114.3 (0.79" ~ 4.5") for peel or cutter mode	
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)	
Media core diameter	25.4 mm or 38.1 mm (1" or 1.5")	
Label length	5 ~ 2,794 mm (0.2" ~ 110")	5 ~ 1,016 mm (0.2" ~ 40")
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing	
Safety regulation	FCC Class A, CE Class A, RCM Class A, cTUVus, TÜV/safety, CCC, BIS, KC, BSMI, EAC, ENERGY STAR®	
Environmental concern	Comply with RoHS, REACH, WEEE	
Accessories	• Windows labeling software CD disk • Quick start guide • USB cable • Power cord	
Limited warranty	• Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first	
Dealer options	• Peel-off kit • Regular guillotine cutter (full cut) • Internal Bluetooth 4.2 • 802.11 a/b/g/n wireless module (for device without slot-in housing)*	
User options	• KP-200 Plus keyboard display unit • 802.11 a/b/g/n wireless module (for device with slot-in housing)*	



CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tsprinters.com

LIIZE PLANT

TSC Auto ID Technology Co., Ltd.
Tel: +886 3 990 6677
E-mail: apac_sales@tsprinters.com

AMERICAS

TSC Auto ID Technology America Inc.
Tel: +1 657 258 0808
E-mail: americas_sales@tsprinters.com

MEXICO

TSC Mexico Representative Office
Tel: +1 52 (33) 3673 1406
E-mail: americas_sales@tsprinters.com

BRAZIL

TSC Brazil Representative Office
Tel: +55 (11) 3554 7225
E-mail: americas_sales@tsprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH
Tel: +49 (0) 8106 37979 000
E-mail: emea_sales@tsprinters.com

RUSSIA

TSC Auto ID Technology EMEA GmbH
Tel: +7 495 249 9017
E-mail: emea_sales@tsprinters.com

MIDDLE EAST

TSC Auto ID Technology ME Ltd, FZE
Tel: +971 4 2533 069
E-mail: emea_sales@tsprinters.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd.
Tel: +886 2 2218 6789
E-mail: apac_sales@tsprinters.com

INDIA

TSC India Distributor's Office
Tel: +91 2267 082 465
E-mail: apac_sales@tsprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd.
Tel: +86 22 5981 6661
E-mail: apac_sales@tsprinters.com

KOREA

TSC Korea Representative Office
Tel: +82 2 852 3322
E-mail: apac_sales@tsprinters.com

Note: *Either Wireless or Bluetooth interface is available.



TSC® is a trademark of TSC Auto ID Technology Co., Ltd.
TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company.
© 2019 TSC Auto ID Technology Co., Ltd.
Product models and Specifications are subject to change without notice.
Contact your TSC sales representative for specific information.
V0119_02

/// www.tsprinters.com